

# OpenWRT

## config

after each change run

```
/etc/init.d/network restart
```

## ethernet

dhcp (and NAT) on wanbr by default

```
/etc/config/network
```

## wifi

<https://openwrt.org/docs/guide-user/network/wifi/basic>

by default wifi is disabled, so at least the disabled option needs to be changed

```
vi /etc/config/wireless
```

```
config wifi-device 'radio0'
    option type 'mac80211'
    option path 'platform/soc/18000000.wifi'
    option channel '1'
    option band '2g'
    option htmode 'HE20'
    option disabled '1'

config wifi-iface 'default_radio0'
    option device 'radio0'
    option network 'lan'
    option mode 'ap'
    option ssid 'OpenWrt'
    option encryption 'none'

config wifi-device 'radio1'
    option type 'mac80211'
    option path 'platform/soc/18000000.wifi+1'
    option channel '36'
    option band '5g'
    option htmode 'HE80'

config wifi-iface 'default_radio1'
    option device 'radio1'
```

```
option network 'lan'
option mode 'ap'
option ssid 'OpenWrt'
option encryption 'psk2'
option key 12345678
```

/etc/init.d/network restart

## firewall

/etc/config/firewall

at the end of „config defaults“ add

```
option flow_offloading '1'
option flow_offloading_hw '1'
```

maybe set

```
option input ACCEPT
option output ACCEPT
option forward ACCEPT
```

From:

<https://www.fw-web.de/dokuwiki/> - FW-WEB Wiki



Permanent link:

<https://www.fw-web.de/dokuwiki/doku.php?id=en:bpi-r3:openwrt>

Last update: **2023/11/09 19:25**